



# Powder Coated Steel Weighing Scale

# Features

Accuracy: III class  
Specification: (0~30000) d  
Nonlinearity:  $\leq 0.01\%F.S$   
System working voltage: DC:5V  
Division: 1/2/5/10/20/50  
Sampling speed: 10/80 times / second  
Internal resolution: 300000~600000  
Lithium battery: 3.7V 3000mah

AC: Use adapter  
Input: AC 110~240V  
Output: DC 9V/500~600mA

Main system consumption current (sleep state): About 25mA  
Main system consumption current (LCD working state): About 50mA

LOADCELL connection (for indicator)

PIN1: E+            PIN3: S+  
PIN2: E-            PIN5: GND  
PIN4: S-

Protocol specification

This indicator has 25 protocols, combined with menu F9 function, to be used for docking different kinds of guns.

Some of the agreements are as follows:

| Capacity            | Division            | Dimension           |
|---------------------|---------------------|---------------------|
| 1000 kg             | 0,2 kg              | 80 x 80 cm / 1x1 m  |
| 2000 kg             | 0,2 kg              | 122 x 122 cm        |
| 3000 kg             | 0,5 kg              | 122 x 122 cm        |
| 5000 kg             | 1 kg                | 150 x 150 cm        |
| 10000 kg            | 2 kg                | 150 x150 cm         |
| <b>Customizable</b> | <b>Customizable</b> | <b>Customizable</b> |